


## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>5</sup> :</b> <b>A61L 2/12, A61N 2/10</b> <b>H01J 37/20</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 92/19284</b> <b>(43) International Publication Date:</b> 12 November 1992 (12.11.92)
<b>(21) International Application Number:</b> PCT/US92/03422 <b>(22) International Filing Date:</b> 27 April 1992 (27.04.92) <b>(30) Priority data:</b> 697,170                      8 May 1991 (08.05.91)                      US <b>(71) Applicant:</b> BAXTER INTERNATIONAL INC. [US/US]; One Baxter Parkway, Deerfield, IL 60015 (US). <b>(72) Inventors:</b> GRIMM, Daniel, J. ; 2214 Glenwood Court, McHenry, IL 60050 (US). LEUENBERGER, Mark, S. ; 5403 Virginia Court, Gurnee, IL 60031 (US). <b>(74) Agents:</b> PRICE, Bradford, R., L. et al.; Baxter International Inc., One Baxter Parkway, Deerfield, IL 60015 (US).		<b>(81) Designated States:</b> AT (European patent), BE (European patent), CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, LU (European patent), MC (European patent), NL (European patent), SE (European patent).  <b>Published</b> <i>With international search report.</i>

**(54) Title:** CONTAINER FOR IRRADIATION OF BLOOD PRODUCTS

**(57) Abstract**

A container (10) for irradiation comprises a flexible, flat collapsible wall (12, 13) defining a sealed chamber (36), the plastic material of the wall (12, 13) is substantially transparent to irradiation, typically ultraviolet radiation. Access ports (22, 24, 26) are provided for communicating through the wall (12, 13) to the chamber (36). A flap (32) is provided, integral with the wall (12, 13) and spaced from the chamber (36), and carries identifying indicia (38) including a typical bar code indicia (40), so that the wall (12, 13) may be at least substantially free of opaque indicia. Also, structure may be provided for detecting and indicating exposure of the container to irradiation, such as ultraviolet sensitive tape (50) adhering to the flap (32). Alignment holes (46) may be provided, typically in the flap (32), to facilitate orientation of the container (10) with apparatus for irradiation (51) and apparatus for bar code reading (72), making use of alignment pins (70) carried by such apparatus (51).



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HL	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	RU	Russian Federation
CG	Congo	KP	Democratic People's Republic of Korea	SD	Sudan
CH	Switzerland	KR	Republic of Korea	SE	Sweden
CI	Côte d'Ivoire	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SV	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
DE	Germany	MC	Monaco	TG	Togo
DK	Denmark			US	United States of America

## CONTAINER FOR IRRADIATION OF BLOOD PRODUCTS

5

Technical Field

As described in Kahn et al. U.S. Patent No. 4,608,255 entitled Biocompatible Method for in Situ  
10 Production of Functional Platelets and Product Produced  
Thereby Lacking Immunogenicity, it is taught to expose  
blood products which contain substantial numbers of  
platelets to ultraviolet (U.V.) radiation, to eliminate  
or greatly decrease an immune response to the platelet  
15 preparation by alloimmunized patients. It is generally  
believed that this alloimmunization is caused by the  
residual lymphocytes present in the platelet  
concentrations prepared by standard procedures, which  
result in undesired immunological response on the part  
20 of the patient receiving the platelets. The ultraviolet  
irradiation of platelet preparations appears to disable  
the lymphocytes from causing such an undesired immune  
response. The result of this is to prolong the life of  
donated platelets in the blood stream of a patient, for  
25 example cancer patients undergoing chemotherapy or the  
like.

As described in the Kahn et al. patent, a  
platelet suspension in a plastic container, permeable to  
ultraviolet radiation, is exposed to an ultraviolet

dosage. Specifically, a dosage of radiation of about 774 Joules per square meter for about 30 minutes is proposed, using polyethylene, polypropylene, or  
5 polyvinyl chloride bags. The ultraviolet radiation passes through the bag walls to irradiate platelets and other cells present, to provide a cell preparation for administration to the patient which elicits little or no undesirable immune response from the patient.

10 The process of Dr. Kahn has been further improved and refined, particularly through the improvements described in Miripol et al. U.S. Patent Nos. 4,726,949; 4,952,812; and 4,866,282. Specifically, it was found that improvements in the results can be obtained with an  
15 increase in the overall energy of ultraviolet radiation exposure, while improvements in the apparatus for administering ultraviolet radiation to flexible containers of blood product are also disclosed. In accordance with this invention, improvements are  
20 provided in a flexible, flat-collapsible, ultraviolet transparent container for holding the above blood product, any other blood or biological liquid product, or any other material, in sealed manner while it is irradiated with U.V. radiation. Additionally, an  
25 improved apparatus for administering such ultraviolet radiation is disclosed.

In the field of collecting and processing blood components for administration to patients, it is of

course extremely important to provide proper identification and categorization of the various blood component portions. This has been customarily done in the past by printing indicia on the face and tubing of the bag which contains the blood components. However, with respect to the particular blood component at issue here which is to be irradiated with ultraviolet radiation, printed indicia on the bag will serve to block the ultraviolet irradiation of the contents thereof, resulting in unsuccessful ultraviolet irradiation. Accordingly, it is highly preferable for the container to be free of indicia that would block the ultraviolet irradiation of the blood product contents thereof.

At the same time, it is desirable to have a quick and reliable means for indicating that the blood component within the container has or has not been treated with ultraviolet irradiation. Also, the indicia identifying the container desirably include a bar code so that the container and its contents may be tracked and categorized through a computerized inventory control system, which can reduce the danger of misidentification or loss that is more likely with a manual inventory control system.

Accordingly, there is a need for the container to be automatically and properly positioned in the irradiation device so that a bar code can be

automatically read, while at the same time the bar code does not interfere with the ultraviolet irradiation of the contents of the container, and the bar code is not  
5 accidentally positioned in an ultraviolet irradiation apparatus wrongly, or with a misidentification of the contents of the container, or the like.

The above technical issues are addressed and successfully dealt with in the container of this  
10 invention, especially when processed in apparatus as disclosed in this invention, to achieve the many advantages that are available when the above recited technical disadvantages are overcome.

#### 15                   Description of the Invention

In accordance with this invention, a container is provided for the irradiation of blood or other products. The container comprises a flexible, flat-collapsible  
20 wall defining a sealed blood product chamber. Access port means, typically a plurality of conventional access ports, are provided for communicating through the wall to the blood product chamber.

A flap is also provided, integral with the wall  
25 and spaced from the chamber. The flap preferably is made of the same, typically transparent plastic material that the rest of the container wall is made of, carrying a label on or within the plastic flap. The label, in

turn, carries identifying indicia, typically including bar code indicia.

The container wall is made of a plastic material that is substantially transparent to the specific irradiation being used. In the case of ultraviolet radiation, a suitable plastic material for use is poly(ethylene vinyl acetate). Such materials are readily commercially available, and bags of such material are available from the Fenwal division of Baxter International Inc. of Deerfield, Illinois.

It is preferred for the container, and particularly the flap of the container, to carry means for detecting and indicating exposure of the container to the irradiation. Ultraviolet exposure indicating tape or tabs are commercially available, for example from the U.V. Process Supply Co. of Chicago, Illinois.

Additionally, it is preferred for the container, typically within the flap, to define alignment hole means spaced from the chamber for facilitating the orientation of the container with apparatus for irradiation, and also apparatus for bar code reading. Thus, a pair of pins may be appropriately positioned in the irradiation apparatus, and a container in accordance with this invention may be mounted on such a pair of pins by means of a pair of alignment holes appropriately positioned in the flap so that, when the container is so mounted on the alignment holes, the bar code on the flap

is properly positioned to be read by a bar code reader, and the container is properly positioned for irradiation in the apparatus. The bag flap may also carry an area  
5 for receiving handwritten notes or other indicia for added comments and identification by the user.

Thus, a flexible, collapsible container is provided in which the wall of the container which defines a blood product chamber is at least  
10 substantially free of opaque indicia to facilitate the irradiation thereof, while the identifying and describing indicia, typically including a bar code, are positioned on a flap which is spaced from the blood product chamber defined by the container.

15 Additionally, the container can be quickly examined to determine whether it has been exposed to radiation or not by means of the means for detecting and indicating such exposure, and alignment hole means are provided for assuring proper alignment of the container  
20 for appropriate irradiation and bar code reading.

While the container of this invention may be used in conjunction with a large variety of different apparatus for irradiation, the container is preferably used with apparatus for irradiating with ultraviolet  
25 radiation a layer of blood product containing white cells, the layer being defined by the container as it lies on a tray within the apparatus. The apparatus comprises a housing which defines a chamber and a pair



of ultraviolet light sources positioned on opposed sides of the chamber. The housing comprises a pair of housing sections which are moveable in hinged relation between opened and closed positions, each of the sections carrying one of the pair of ultra violet light sources. A manually removable tray is carried within the housing to define a support surface for a flexible container of blood product, such as, but not limited to, the container as described herein. Thus, such a flexible container may be carried in the chamber. The support surface of the tray is made of an ultraviolet-transmissive material such as quartz, so that the container may be irradiated from both sides of the tray by the pair of ultraviolet light sources.

Additionally, the apparatus may carry a bar code reader which is positioned to read bar codes carried on flaps of containers made in accordance with this invention. Typically, the tray carries pin means which are positioned to engage alignment hole means in the containers to be irradiated, so that the container is appropriately aligned for both irradiation and bar code reading.

Description of Drawings

In the drawings, Fig. 1 is a front plan view of  
5 a flexible, collapsible container for the irradiation of  
blood products in accordance with this invention, with  
portions broken away;

Fig. 2 is a perspective view showing bag  
10 irradiating apparatus in open position;

Fig. 3 is a perspective view showing the  
apparatus of Fig. 2 in closed position; and  
15

Fig. 4 is a sectional view taken along line 3-3  
of Fig. 2 showing the manually removable, internal tray  
of the apparatus receiving a flexible, collapsible  
container of blood product.

20

Description of Specific Embodiments

Referring to Fig. 1, a flexible, collapsible  
container 10 for the irradiation of blood is disclosed.  
25 Container 10 may be made in accordance with  
substantially conventional design, except as otherwise  
described herein, being made of a pair of peripherally  
heat sealed sheets of poly (ethylene vinyl acetate) 12,

13, peripherally sealed together by a radio frequency heat seal or other type of seal line 14.

Container 10 defines a major longitudinal axis 16  
5 between container ends 18, 20, with three access ports 22, 24, 26 being defined at one end thereof in conventional manner. Central access port 24 connects to a short length of flexible tubing 28, which terminates in a conventional spike connector 30. The other two  
10 access ports are connected to short, semi-rigid, tubular ports containing a spike puncturable diaphragm in conventional manner, being closed by conventional D-ring port protectors as described, for example, in U.S. Patent No. 4,573,980 and as commercially used on other  
15 medical containers.

At the end 20 of container 12, a flap 32 is defined, being spaced from the chamber 36 defined within peripheral seal line 14 by peripheral seal line portion 34. Flap 32 may be made from an integral piece of  
20 plastic sheets 12, 13, being connected by another peripheral seal line 37 to carry a printed label or card 38 on or within flap 32. As shown, printed label 38 carries various desired indicia, including a bar code 40, which is readable by a conventional bar code reader  
25 through the transparent plastic of plastic layer 13.

Hanger hole 42 may be cut out of the two joined plastic layers 12, 13, and reinforced by an extension 44 of the peripheral seal line 37 about flap 32.

Flap 32 also defines a pair of punched holes 46, which are positioned to be received on prongs or rods carried in the irradiation apparatus for which container 5 10 is made, to properly position container 10 in a manner so that bar code 40 is read by a bar code reader carried in the irradiation apparatus, and also to assure proper positioning of chamber 36 for proper ultraviolet irradiation.

10           Additionally, flap 32 may carry a small amount of ultraviolet sensitive color label or tape 50, which tape is commercially available and which changes color upon substantial ultraviolet exposure. Tape 50 is positioned on the outer surface of plastic layer 13, and may be 15 protected by a protective flap 51, which is removed prior to ultraviolet exposure. For example, one commercially available ultraviolet indicator tape is green if unexposed, but turns to magenta if exposed to substantial ultraviolet radiation.

20           On the reverse side of flap 32, a paper label 53 may be adhered to the outer surface of plastic layer 12, to permit the user to write notes or indicating indicia with a pen or pencil.

          It can be seen that the bulk of container 10, 25 particularly the container walls surrounding chamber 36, is free of any opaque indicia, with all of the indicia being carried in the flap. Thus, there is no

interference with the ultraviolet irradiation of the contents of the container.

Turning to Figs. 2-4, an apparatus for the  
5 irradiation of the container of Fig. 1 is disclosed. Apparatus 51 comprises a housing which defines an internal chamber 54, with banks of ultraviolet lights 56, 58 carried on opposed sides of chamber 54 by the housing.

10 Housing 52 comprises a pair of housing sections 60, 62 which are connected together on one side with hinges 64 so that the housing sections are movable in hinged relation between an open position as shown in Fig. 3 and a closed position as shown in Fig. 4, with  
15 the ultraviolet irradiation taking place in the closed position. Each of sections 60, 62 carries one of the banks of ultraviolet lights 56, 58 plus conventional circuitry for operating them, being connected to a control panel 59 carried on the apparatus.

20 A manually removable tray 65 is provided to fit within the housing sections of apparatus 51 when the apparatus is in its closed position. Thus, the apparatus can be opened, and the tray 65 may be removed and replaced with ease, the tray being appropriately  
25 positioned so that both sides of it are irradiated by the ultraviolet light banks 56, 58.

Tray 64 defines a frame 66 and a bottom wall or floor 68, the later being made of quartz to be

ultraviolet transmissive. Thus, a flexible, collapsible container 10 such as that shown in Fig. 1 may be placed on the floor 68 of the tray to form a layer of blood product which is spread out to the degree permitted by the flexible collapsible container. Then, tray 65 is placed into irradiation apparatus 51 while the apparatus is in open position, and then the housing sections 60, 62 may be closed by pivotable hinged motion into their closed configuration as in Fig. 3. The ultraviolet light banks are then actuated for a predetermined time as set by means of the apparatus controls.

Tray 65 defines a set of pins 70 which may be positioned to pass through holes 46 of collapsible container 10 to properly position the container within apparatus 51. Thus, with such proper positioning, chamber 36 is properly positioned for optimum exposure to ultraviolet light from light banks 56, 58, while bar code 40 is positioned for proper reading by a bar code reader 72, carried by housing section 60. The protective cover 51 is removed from ultraviolet sensitive tape 50 prior to the ultraviolet irradiation.

Thus, through a software driven system which may be included in or connected to apparatus 51, the bar code reader can cross check with other data to be sure that the contents of bag 10 are being properly treated, and that the identity of the contents of bag 10 has been verified. Appropriate information from the bar code can

be read out or printed out for the users as may be desired. The system may be disabled if the bar code is not that which was expected by the program.

5           After the ultraviolet irradiation has taken place, apparatus 51 may be opened, and tray 64 may be removed, for the easy removal of container 10, and optional replacement with another container 10 containing another portion of blood product.

10           Thus, ultraviolet irradiating apparatus and a container for use therein is disclosed, having significant advantages based on automated monitoring of the identity of the blood product being irradiated, for added reliability of identification of the blood  
15 product, to further provide the confidence that blood products will not become mixed up or processed wrongly. Additionally, one can tell from a glance whether the container has been U.V. irradiated or not, as a further cross check against undesired double irradiation or  
20 failure to irradiate. At the same time, while all desired identifying indicia may be applied to the bag, the chamber that holds the blood product is not shadowed and shielded from ultraviolet irradiation by any indicia carried on the wall that surrounds the chamber.

25           The above has been offered for illustrative purposes only, and is not intended to limit the scope of the invention of this application, which is as defined in the claims below.

THAT WHICH IS CLAIMED IS:

1. A container for the irradiation of liquids  
5 which comprises a flexible, flat-collapsible wall  
defining a sealed chamber; access port means for  
communicating through said wall to the chamber; and a  
flap, integral with said wall and spaced from said  
chamber, said flap carrying identifying indicia  
10 including bar code indicia, said wall being made of a  
plastic material that is substantially transparent to  
said irradiation.

2. The container of Claim 1 in which said flap  
15 carries means for detecting exposure of said container  
to said irradiation.

3. The container of Claim 1 which contains  
alignment hole means spaced from said chamber for  
20 facilitating the orientation of said container with  
apparatus for said irradiation and apparatus for bar  
code reading.

4. The container of Claim 1 in which said wall  
25 which defines the chamber is at least substantially free  
of opaque indicia.



5. The container of Claim 1 in which said flap carries an area for receiving handwritten notes.

5           6. The container of Claim 1 in which said container defines a major, longitudinal axis between container ends, said access port means being carried on one of said container ends and said flap being carried on the other of said container ends.

10


7. Apparatus for irradiating materials, which comprises:

          a housing which defines a chamber and a pair of ultraviolet light sources positioned on opposed sides of  
15 said chamber, said housing comprising a pair of housing sections moveable in hinged relation between open and closed positions, each section carrying one of said pair of said ultraviolet light sources;

          a manually removable tray carried within said  
20 housing to define a support surface for a flexible container of in said chamber, said support surface being made of an ultraviolet-transmissive material.

8. The apparatus of Claim 7 in which each  
25 ultraviolet light source comprises a plurality of ultraviolet light bulbs.

1/2



2/2

FIG. 2




FIG. 3





FIG. 4



# INTERNATIONAL SEARCH REPORT

International Application No. PCT/US92/03422

## I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all)<sup>3</sup>

According to International Patent Classification (IPC) or to both National Classification and IPC

IPC (5): A61L 2/12; A 61N 2/10; H01J 37/20  
US CL : 422/24; 604/408; 250/491.1

## II. FIELDS SEARCHED

Minimum Documentation Searched <sup>4</sup>	
Classification System	Classification Symbols
U.S.	422/24, 102; 604/408, 404, 415; 250/491.1, 491.2, 455.1

Documentation Searched other than Minimum Documentation  
to the extent that such Documents are included in the Fields Searched<sup>5</sup>

## III. DOCUMENTS CONSIDERED TO BE RELEVANT<sup>14</sup>

Category <sup>6</sup>	Citation of Document, <sup>16</sup> with indication, where appropriate, of the relevant passages <sup>17</sup>	Relevant to Claim No. <sup>18</sup>
Y	US, A, 3,915,212 (Bujan et al) 28 October 1975, see entire document.	1-6, 11-14 & 20
Y	US, A, 3,694,651 (Glasson) 26 September 1972, see entire document.	7-10
A	US, A, 4,561,110 (Herbert) 24 December 1985, see entire document.	1-6, 11-14 & 20
Y	US, A, 4,726,949 (Miripol et al) 23 February 1988, see entire document.	7-10 & 15-19
A	US, A, 4,804,363 (Valeri) 14 February 1989, see entire document.	1-6, 11-14 & 20
Y	US, A, 4,866,282 (Miripol et al) 12 September 1989, see entire document.	7-10 & 15-19
A	US, A, 4,880,425 (Kuhlemann et al) 14 November 1989, see entire document.	1-6, 11-14 & 20
A	US, A, 4,917,684 (Yasumura) 17 April 1990, see entire document.	1-6, 11-14 & 20
Y	US, A, 4,952,812 (Miripol et al) 28 August 1990, see entire document.	7-10 & 15-19

\* Special categories of cited documents:<sup>15</sup>

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

## IV. CERTIFICATION

Date of the Actual Completion of the International Search <sup>2</sup>	Date of Mailing of this International Search Report <sup>2</sup>
26 JUNE 1992	22 JUL 1992
International Searching Authority <sup>1</sup>	Signature of Authorized Officer <sup>20</sup>
ISA/US	L. KUMMERT

## FURTHER INFORMATION CONTINUED FROM THE SECOND SHEET

A	US, A, 4,994,039 (Mattson) 19 February 1991, see entire document.	1-6, 11-14 20
X	Photocopy of Baxter Transfer Pack Container, Copyright notice of the year 1989, Baxter Healthcare Corporation, Deerfield, IL.	1-6, 11-14 20
X	Operator's Manual - Fenwal Ultraviolet Irradiation System, Copyright 1990, Baxter Healthcare Corporation, Deerfield, IL.	1-20

V. ☐ OBSERVATIONS WHERE CERTAIN CLAIMS WERE FOUND UNSEARCHABLE<sup>1</sup>

1. ☐ Claim numbers , because they relate to subject matter (1) not required to be searched by this Authority, namely:
2. ☐ Claim numbers , because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out (1), specifically:
3. ☐ Claim numbers , because they are dependent claims not drafted in accordance with the second and third sentences of PCT Rule 6.4(a).

VI. ☒ OBSERVATIONS WHERE UNITY OF INVENTION IS LACKING<sup>2</sup>

This International Searching Authority found multiple inventions in this international application as follows:  
Please See Attached Sheet.

1. ☒ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims of the international application. (Telephone Practice)
2. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims of the international application for which fees were paid, specifically claims:
3. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claim numbers:
4. ☐ As all searchable claims could be searched without effort justifying an additional fee, the International Search Authority did not invite payment of any additional fee.

Remark on protest

- ☐ The additional search fees were accompanied by applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

## FURTHER INFORMATION CONTINUED FROM PREVIOUS SHEETS

VI. OBSERVATIONS WHERE UNITY OF INVENTION WAS LACKING  
This ISA found multiple inventions as follows:

- Group I. Claims 1-6, 11-14 & 20, drawn to a container, classified in Class 604, subclass 408.
- Group II. Claims 7-10, drawn to an apparatus for irradiating materials, classified in Class 250, subclass 491.1.
- Group III. Claims 15-19, drawn to a method of using an irradiating apparatus, classified in Class 422, subclass 24.
- The claims of these three groups are directed to different inventions which are not so linked as to form a single general inventive concept, since the method does not require the particulars of either of the apparatus and each of the apparatus can be used to perform another and materially different method.